

LETTER SIZE vs. DISTANCE

VIEWING EXPOSURE IN SECONDS

character height	optimal viewing distance	max viewing distance	speed 20mph	30mph	40mph	50mph	60mph
3"	30'	100′	3.4s	2.5s	1.7s	1.3s	0.9s
4"	40'	150′	5.1s	3.4s	2.5s	2.0s	1.4s
6"	60'	200′	6.8s	4.5s	3.4s	2.7s	1.9s
8"	80'	350′	12.0s	7.9s	5.9s	4.7s	3.4s
9"	90'	400′	13.6s	9.0s	6.8s	5.4s	3.8s
10"	100′	450′	15.3s	10.2s	7.6s	6.1s	4.3s
12"	120′	525′	17.9s	11.9s	8.9s	7.1s	5.1s
15"	150′	630′	21.5s	14.3s	10.7s	8.5s	6.1s
18"	180′	750′	25.59s	17.0s	12.7s	10.2s	7.3s
24"	240′	1000′	34.1s	22.7s	17.0s	13.6s	9.7s
30"	300′	1250′	42.6s	28.4s	21.3s	17.0s	12.1s
36"	360′	1500′	51.1s	34.0s	25.5s	20.4s	14.6s
42"	420′	1750′	59.7s	39.7s	29.8s	23.8s	17.0s
48"	480′	2000′	68.2s	45.4s	34.1s	27.2s	19.4s
60"	600′	2500′	85.3s	56.81s	42.6s	34.1s	24.3s

A sans serif typeface with medium stroke is used for measuring (such as arial bold). Based on black letters with a white background. Distance may vary 10% with various color combinations. Viewing ranges are approximate.



More than 50 Years of

Leading the Way
Signage Innovation
A Trusted Partner
A Partner with Impeccable Values

Custom | Interior | Exterior | Digital

Contact us! asisignage.com | 800.274.7732